



HARFA VINTAGE





PRODUCT DETAILS

Surface structure Irregularly cross-sawn
Finish Osmo PolyX® + Osmo PolyX® top-coating

Engineered Wood - 14/3 mm - T&G

| | | | | | | |
|---|---|--------------------|---|-----|-----|---|
|  |  <p>SINGLE STRIP • 2V</p> <p>* Also available in 15/4mm (except Calm grading)</p> | Length (mm) | 85% m ² 1720-2400mm 15% m ² 500-1520mm | | | |
| | | Width (mm) | 190* | 225 | 245 | |
| | | Grading | Special Rustic | • | • | • |
| | | | Original | • | • | • |
| | | | Calm | • | | |
| | | | Superb | • | | |
| | | | Elegance | • | | |
| | | | Superb/ Elegance | | • | • |

| | | | | |
|---|--|--------------------|---------------------|-----|
|  |  <p>HERRINGBONE • 4V</p> | Length (mm) | 600 | 700 |
| | | Width (mm) | 100/120 | 175 |
| | | Grading | Special Rustic | • |
| | | | Original | • |
| | | | Superb/ Elegance | • |

TECHNICAL PROPERTIES

| | Test Method | Solid 20mm | 3-layer 14mm | 3-layer 15mm |
|---|--|---------------------------|---------------------------|---------------------------|
| Production standard & Conformity | EN 14342, EN 13489, EN 13488 EN 13629, EN 13226 | Implemented | Implemented | Implemented |
| Moisture content | ČSN EN 13183-1 | 9 ±2% | 7 ±2% | 7 ±2% |
| Formaldehyde emission | ČSN EN 717-1 | E1 | E1 | E1 |
| PCP (pentachlorophenol) | CEN/TR 14823 | ≤ 5 ppm | ≤ 5 ppm | ≤ 5 ppm |
| Slip resistance | CEN/TS 15676 | Dry ≥ 69 Wet ≥ 29 | Dry ≥ 69 Wet ≥ 29 | Dry ≥ 69 Wet ≥ 29 |
| Reaction to fire | ČSN EN 13501-1 | Cfl-s1 | Dfl-s1 | Cfl-s1 |
| Thermal resistance | ČSN EN ISO 10456 | 0,15 m ² · K/W | 0,11 m ² · K/W | 0,12 m ² · K/W |
| Thermal conductivity | ČSN EN ISO 10456 | 0,13 W/mK | 0,13 W/mK | 0,13 W/mK |
| Biological durability | ČSN EN 335 | Class 1 | Class 1 | Class 1 |
| Underfloor heating | | Not recommended | Up to 225 mm | Up to 225 mm |
| Recommended usage | Suitable for interior use in all project sectors: residential-commercial-hospitality-retail. Actual warranty & maintenance instructions apply | | | |
| Well-managed forests | This product is made with PEFC certified wood | | | |

For more details, see <https://www.escoflooring.com>

ESCO General Terms and conditions apply, see <https://www.escoflooring.com>



DECOSPAN.